

XP 95 PLUS

4WD Backhoe Loader

Extendable
Dipper Arm

AC Cabin

Smart Hydraulic
to Optimize
Engine Power

6 in 1
Multipurpose
Bucket

Higher
Breakout Force
& Digging Depth

Out Rigger Alarm
with Broader
Foot Pad

Four Wheel
Drive (4WD)

Closed Engine
Hood Cover



**Modern
AC Cabin**



**Highest
Dump Height**



**Highest Tear
& Breakout Force**



**Cold Start
Engine Kit**




**Extending
Dipper Arm**

XP 95 PLUS

4WD Backhoe Loader

DELCO
Built to Last



ENGINE

- Proven, powerful and fuel efficient KOEL 4R1040TC, water cooled diesel engine. [Perkins engine 1104D-44TA (Optional)]
- Gross power 95 HP at 2200 rpm
- Max torque (gross) : 300 Nm @ 1500 ± 100 rpm

TRANSMISSION

- Four speed (4F, 2R gear) Syncro shift reversing shuttle transmission provides superior traction, gradeability, higher force while entering pile or during dozing operation
- Neutral start provisions prevents starting shuttle is engaged.

STATIC DIMENSIONS

A	: Overall length (transport mode)	6.28 m
	: Overall length (travel mode)	7.85 m
B	: Wheel base	2.14 m
C	: Rear wheel to slew center	1.38 m
D	: Minimum ground clearance	0.35 m
E	: Slew ground clearance	0.59 m
G	: Height to top of cab	2.90 m
H	: Overall height (Standard Dipper)	3.78 m
	: Overall height (Extendable Dipper)	4.04 m
J	: Track width - Rear	1.75 m
K	: Track width - Front	1.87 m
L	: Width (Transport mode)	2.56 m

LOADER PERFORMANCE

M	: Dump height (cutting edge)	3.00 m
N	: Load over height (cutting edge)	3.51 m
O	: Pin height	3.72 m
P	: Pin forward reach	0.43 m
Q	: Reach at ground	1.57 m
R	: Max. reach at full height	1.22 m
S	: Reach at full height - bucket dumped	0.85 m
T	: Below ground level dig depth	0.11 m
U	: Rollback at ground	45 deg
V	: Dump angle	45 deg
	: Bucket breakout force	6425 kgf
	: Loader arm breakout force	5777 kgf
	: Lifting capacity	1980 kg
	: Return to dig	Available
	: Self leveling	Available
	Loader bucket capacity	1.2 m³

EXCAVATOR PERFORMANCE

	Standard Dipper	Extendable Dipper
A	: Max dig depth	4.80 m / 6.01 m
B	: Reach ground level to rear wheel centre	6.97 m / 8.14 m
C	: Reach ground level to slew center	5.65 m / 6.77 m
D	: Reach at full height to slew center	2.23 m / 3.31 m
E	: Side reach to center line of machine	6.00 m / 7.31 m
F	: Max. working height (Stab's fully out)	6.30 m / 6.93 m
G	: Max load over height (Stab's fully out)	4.39 m / 5.13 m
H	: King post travel	1.00 m / 1.00 m
J	: Bucket rotation	187 ° / 187 °
	: Bucket tear out force	6018 kgf / 6018 kgf
	: Dipper tear out force	3250 kgf / 2072 kgf
	: Lift capacity of bucket at full reach (SAE J31)	1554 kg / 850 kg
	: Excavator Bucket Capacity	0.26 Cum / 0.18 Cum

OPTIONAL ATTACHMENTS

- Heavy duty rear tyres : 14x25-20 PR
- Rock breaker piping kit
- Extensible dipper
- Trenching Buckets-0.09 Cum, 0.12 Cum, 0.18 Cum
- Special purpose buckets 0.30 Cum, 0.32 Cum
- Coal buckets - 1.50 Cum
- Ripper tooth
- A.C. Cabin

Channel Partner

The information contained in this leaflet is intended to be of general nature only. We reserve the right to change the specifications without any prior notice. All dimensions and weights are variable with in ±2.5%